# FF521BLBI7SSHV

34" x 19.25" x 21.38" (H x W x D)

Commercially listed 20" wide built-in undercounter all-refrigerator, auto defrost with a lock, stainless steel door, thin handle and black cabinet

## Highlights:

Flexible design allows built-in or freestanding use in 20" wide spaces

ETL-S listed for commercial use

Factory installed lock provides security you can count on

## Product Features:

| | |
|---|---|
| Slim 20" width | Full 4.1 cu.ft. capacity inside conveniently slim footprint |
| Commercially listed | ETL-S listed to NSF standards for commercial use |
| Built-in capable | Make the best use of space by installing your appliance under the counter |
| Factory installed lock | Top-mounted for convenient security |
| Stainless steel wrapped door | Durable 304 grade wrapping |
| Professional handle | Thin 14mm diameter on vertical stainless steel handle |
| Fully finished black cabinet | Allows the unit to be used freestanding |
| Automatic defrost | Reduced maintenance with auto defrost system |
| Hospital grade cord with 'green dot' plug | Secure three-pronged cord for added unit safety |

# FF521BLBI7SSHV Specifications:

| Overview | |
|---|---|
| Height of Cabinet | 33.5" (85 cm) |
| Height to Hinge Cap | 34.0" (86 cm) |
| Width | 19.25" (49 cm) |
| Depth | 21.38" (54 cm) |
| Depth with door at 90° | 39.5" (100 cm) |
| Capacity | 4.1 cu.ft. (116 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Black |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Amps | 1.4 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 64.0 lbs. (29 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101035680 |
| **Refrigerator Features** | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Height Adjustable | 1 |
| Crisper Qty | 1 |
| Crisper Finish | Transparent |
| Crisper Cover | Glass |
| Shelf Type | Glass |
| Shelf Qty | 3 |
| Adjustable Shelves | Yes |
| Thermostat Type | Dial |
| Refrigerant Type | R134a |
| Refrigerant Amount | 1.75oz. |
| High Side PSI | 205.0 |
| Low Side PSI | 103.0 |
| Level Legs Qty | 2 |
| Interior Light | Yes |
| **Dimensions** | |
| Interior Height | 28.5" (72 cm) |
| Interior Width | 15.75" (40 cm) |
| Interior Depth | 18.0" (46 cm) |
| Compressor Step Height | 8.0" (20 cm) |
| Compressor Step Width | 17.0" (43 cm) |
| Compressor Step Depth | 6.75" (17 cm) |

**SUMMIT APPLIANCE DIVISION**, FELIX STORCH, INC. | ISO 9001:2015 Certified
770 Garrison Avenue Bronx, NY 10474 USA **TEL** 718-893-3900 **FAX** 844-478-8799 info@summitappliance.com **www.summitappliance.com**