

FS20L7PLUS



19.75" x 19.75" x 19.38" (H x W x D)

Commercially approved compact all-freezer, manual defrost with a lock and thermometer

Highlights:

- Commercially listed to NSF-7 standards
- Compact cube size is ideal for countertop use
- Factory installed lock provides security you can count on

Product Features:

Commercially approved	ETL-S listed to NSF standards for commercial use
Factory installed lock	Keyed lock for secure interior
Compact dimensions	Ideal size for use on top of counters
Thermometer	Thermometer provides external readout of current and high/low temperatures
-20° capable	Low temperature capability ideal for certain sensitive items
Manual defrost	Efficient performance with reliable temperature stability
Removable shelf	Wired shelf provided
100% CFC Free	Environmentally friendly design with no ozone-damaging chemicals

FS20L7PLUS Specifications:

Overview	
Height of Cabinet	19.75" (50 cm)
Width	19.75" (50 cm)
Depth	19.38" (49 cm)
Depth with door at 90°	37.88" (96 cm)
Capacity	1.6 cu.ft. (45 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.43
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101031699
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	14.5" (37 cm)
Interior Width	15.5" (39 cm)
Interior Depth	15.0" (38 cm)
Shelf Qty	1
Adjustable Shelves	Yes
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	3.17 oz.
High Side PSI	250.0
Low Side PSI	88.0
Level Legs	2
Compressor Step Height	8.5" (22 cm)
Compressor Step Width	15.5" (39 cm)
Compressor Step Depth	7.0" (18 cm)

