

# FS20LCSSMEDDT



20.75" x 19.75" x 21" (H x W x D)

Compact -20°C all-freezer in stainless steel with lock, alarm, digital thermostat, and hospital grade cord

### Highlights:

Compact cube size is ideal for countertop use

Factory installed lock provides security you can count on

-20°C capable with manual defrost operation

### Product Features:

Compact dimensions	Ideal size for use on top of counters
Complete stainless steel exterior	Fully wrapped in 304 grade stainless steel
-20° capable	Low temperature capability ideal for certain sensitive items
Factory installed lock	Keyed lock for secure interior
Digital thermostat	Electronic controls for more precise temperature management
High temperature alarm	Warns of temperature fluctuations and includes an external temperature readout on the door
Manual defrost	Efficient performance with reliable temperature stability
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Factory installed lock	Keyed lock for secure interior

## FS20LCSSMEDDT Specifications:

Overview	
Height of Cabinet	20.75" (53 cm)
Height to Hinge Cap	20.75" (53 cm)
Width	19.75" (50 cm)
Depth	21.0" (53 cm)
Depth with Handle	21.0" (53 cm)
Depth with door at 90°	39.5" (100 cm)
Capacity	1.6 cu.ft. (45 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.43
Voltage/Frequency	115 V AC/60 Hz
Shipping Weight	60.0 lbs. (27 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	14.5" (37 cm)
Interior Width	15.5" (39 cm)
Interior Depth	15.0" (38 cm)
Shelf Qty	1
Adjustable Shelves	Yes
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	3.17 oz.
High Side PSI	250.0
Low Side PSI	88.0
Level Legs	2
Compressor Step Height	8.5" (22 cm)
Compressor Step Width	15.5" (39 cm)
Compressor Step Depth	7.0" (18 cm)

