

FS22L7MEDDT



20.5" x 17.38" x 19" (H x W x D)

Commercially listed compact -20° C all-freezer with digital thermostat, lock, alarm with temperature display, and hospital grade cord

Highlights:

- Commercially listed to NSF-7 standards
- Compact size is ideal for countertop use
- 20°C capable with manual defrost operation

Product Features:

Commercially listed	CSA-S listed to NSF-7 standards
Compact dimensions	Ideal size for use on top of counters
-20° capable	Low temperature capability ideal for certain sensitive items
Manual defrost	Efficient performance with reliable temperature stability
Digital thermostat	Electronic controls for more precise temperature management
Factory installed lock	Keyed lock for secure interior
High temperature alarm	Warns of temperature fluctuations and includes an external temperature readout on the door
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Removable shelf	Wired shelf provided

FS22L7MEDDT Specifications:

Overview	
Height of Cabinet	20.13" (51 cm)
Height to Hinge Cap	20.5" (52 cm)
Width	17.38" (44 cm)
Depth	19.0" (48 cm)
Capacity	1.42 cu.ft. (40 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	CSA
Sanitation	CSA-S
Amps	1.2
Voltage/Frequency	115 V AC/60 Hz
Weight	40.0 lbs. (18 kg)
Shipping Weight	55.0 lbs. (25 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	14.5" (37 cm)
Interior Width	12.38" (31 cm)
Interior Depth	14.5" (37 cm)
Shelf Type	Wire
Shelf Qty	1
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	1.67 oz.
High Side PSI	270.0
Low Side PSI	103.0
Level Legs	2
Compressor Step Height	7.0" (18 cm)
Compressor Step Width	12.38" (31 cm)
Compressor Step Depth	6.0" (15 cm)

