

FS22L7PLUS



20.5" x 17.38" x 19" (H x W x D)

Commercially listed compact all-freezer, manual defrost with a lock and thermometer

Highlights:

Compact size is ideal for countertop use

Commercially listed to NSF-7 standards

Factory installed lock provides security you can count on

Product Features:

Commercially listed	CSA-S listed to NSF-7 standards
Compact dimensions	Ideal size for use on top of counters
Factory installed lock	Keyed security for a secure interior
-20° capable	Low temperature capability ideal for certain sensitive items
Thermometer	Thermometer provides external readout of current and high/low temperatures
Manual defrost	Efficient performance with reliable temperature stability
Removable shelf	Wired shelf provided
Adjustable thermostat	Rear mounted to prevent accidental adjustments
100% CFC Free	Environmentally friendly design with no ozone-damaging chemicals

FS22L7PLUS Specifications:

Overview	
Height of Cabinet	20.13" (51 cm)
Height to Hinge Cap	20.5" (52 cm)
Width	17.38" (44 cm)
Depth	19.0" (48 cm)
Capacity	1.42 cu.ft. (40 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	CSA
Sanitation	CSA-S
Amps	1.2
Voltage/Frequency	115 V AC/60 Hz
Weight	40.0 lbs. (18 kg)
Shipping Weight	55.0 lbs. (25 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101041322
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	14.63" (37 cm)
Interior Width	12.38" (31 cm)
Interior Depth	14.5" (37 cm)
Shelf Type	Wire
Shelf Qty	1
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	1.67 oz.
High Side PSI	270.0
Low Side PSI	103.0
Level Legs	2
Compressor Step Height	7.0" (18 cm)
Compressor Step Width	12.38" (31 cm)
Compressor Step Depth	6.0" (15 cm)

