accuc@ld

FS22LGL7



20.88" x 17.38" x 19" (H x W x D)

Compact commercially listed all-freezer w/glass door and

Highlights:

Commercially listed to NSF-7 standards

Glass door provides full view of interior

Seamless interior liner simplifies cleanup

Product Features:

| Commercially listed | CSA-S listed to NSF standards for commercial use |
|------------------------------|---|
| Glass door | Provides full display of stored contents |
| Factory installed lock | Keyed lock for a secure interior |
| Fully finished white cabinet | Allows the unit to be used freestanding |
| -20º C capable | Low temperature operation is ideal for temperature sensitive materials |
| Manual defrost | No temperature fluctuations with a manual defrost system that keeps the cold inside |
| Adjustable thermostat | Rear mounted to prevent accidental adjustments |
| Removable shelf | Wire shelf for storage convenience |
| One piece interior liner | Easy clean-up with a seamless liner that won't hold a mess in hidden crevices |

accuc@ld

FS22LGL7 Specifications:

| Overview | | | |
|--|---|--|--|
| Height of Cabinet | 20.5" (52 cm) | | |
| Height to Hinge Cap | 20.88" (53 cm) | | |
| Width | 17.38" (44 cm) | | |
| Depth | 19.0" (48 cm) | | |
| Capacity | 1.42 cu.ft. (40 L) | | |
| Defrost Type | Manual | | |
| Door | Glass | | |
| Cabinet | White | | |
| US Electrical Safety | CSA | | |
| Sanitation | CSA-S | | |
| Amps | 1.2 | | |
| Voltage/Frequency | 115 V AC/60 Hz | | |
| Weight | 40.0 lbs. (18 kg) | | |
| Shipping Weight | 55.0 lbs. (25 kg) | | |
| Parts & Labor Warranty | 1 Year | | |
| Compressor Warranty | 5 Years | | |
| UPC | 761101027234 | | |
| Freezer | | | |
| Door Swing | RHD | | |
| Reversible | Yes | | |
| Interior Height | 14.63" (37 cm) | | |
| | (/ | | |
| Interior Width | 12.38" (31 cm) | | |
| Interior Width Interior Depth | | | |
| | 12.38" (31 cm) | | |
| Interior Depth | 12.38" (31 cm) 14.5" (37 cm) | | |
| Interior Depth Shelf Type | 12.38" (31 cm) 14.5" (37 cm) Wire | | |
| Interior Depth Shelf Type Shelf Qty | 12.38" (31 cm) 14.5" (37 cm) Wire | | |
| Interior Depth Shelf Type Shelf Qty Thermostat Type | 12.38" (31 cm) 14.5" (37 cm) Wire 1 | | |
| Interior Depth Shelf Type Shelf Qty Thermostat Type Refrigerant Type | 12.38" (31 cm) 14.5" (37 cm) Wire 1 Dial R134a | | |
| Interior Depth Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount | 12.38" (31 cm) 14.5" (37 cm) Wire 1 Dial R134a 1.67 oz. | | |
| Interior Depth Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI | 12.38" (31 cm) 14.5" (37 cm) Wire 1 Dial R134a 1.67 oz. 270.0 | | |
| Interior Depth Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI | 12.38" (31 cm) 14.5" (37 cm) Wire 1 Dial R134a 1.67 oz. 270.0 103.0 | | |
| Interior Depth Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs | 12.38" (31 cm) 14.5" (37 cm) Wire 1 Dial R134a 1.67 oz. 270.0 103.0 | | |
| Interior Depth Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Compressor Step Height | 12.38" (31 cm) 14.5" (37 cm) Wire 1 Dial R134a 1.67 oz. 270.0 103.0 2 7.0" (18 cm) | | |



