

FS408BLBI7FR



34" x 19.25" x 21.38" (H x W x D)

Commercially listed 20" wide built-in undercounter allfreezer, -20° C capable with a lock and stainless steel door frame for slide-in custom panels

Highlights:

ETL-S listed for commercial use

Flexible design allows built-in or freestanding use in 20" wide spaces

Factory installed lock provides security you can count on

Product Features:

Slim 20" width	2.8 capacity inside a slim footprint	
Commercially listed	ETL-S listed to NSF standards for commercial use	
Built-in capable	Make the best use of space by installing your appliance under the counter	
Fully finished black cabinet	Allows the unit to be used freestanding	
Factory installed lock	Top-mounted for convenient security	
Stainless steel door frame	Two-piece "U"-shaped door frame accepts slide-in custom panels (panel size: 19 1/4" W x 31 1/4" H at up to 1/4" thick)	
Reversible door	Keep your options flexible with a reversible door that is easy to switch when your arrangement changes	
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety	
Manual defrost	Efficient performance with reliable temperature stability	







FS408BLBI7FR Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Height to Hinge Cap	34.0" (86 cm)
Width	19.25" (49 cm)
Depth	21.38" (54 cm)
Depth with door at 90°	39.5" (100 cm)
Capacity	2.8 cu.ft. (79 L)
Defrost Type	Manual
Door	Panel-Ready
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.6
Voltage/Frequency	115 V AC/60 Hz
Weight	64.0 lbs. (29 kg)
Shipping Weight	67.0 lbs. (30 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101036885
Freezer	
Door Swing	RHD
Reversible	Yes
Height Adjustable	1
Interior Height	26.38" (67 cm)
Interior Width	14.0" (36 cm)
Interior Depth	16.75" (43 cm)
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	3.0 oz.
High Side PSI	210.0
Low Side PSI	105.0
Level Legs	2
Interior Drawers	Yes



