

## FS408BLBI7SSHV



34" x 19.25" x 21.38" (H x W x D)

Commercially listed 20" wide built-in undercounter allfreezer, -20° C capable with a lock, stainless steel door, thin handle and black cabinet

## **Highlights:**

Flexible design allows built-in or freestanding use in 20" wide spaces

ETL-S listed for commercial use

-20° C capable with interior slide-out drawers for easy storage

## **Product Features:**

Slim 20" width	2.8 capacity inside a slim footprint	
Commercially listed	ETL-S listed to NSF standards for commercial use	
Built-in capable	Make the best use of space by installing your appliance under the counter	
Fully finished black cabinet	Allows the unit to be used freestanding	
Factory installed lock	Top-mounted for convenient security	
Stainless steel wrapped door	Durable 304 grade wrapping	
Professional handle	Thin 14mm diameter on vertical stainless steel handle	
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety	
Manual defrost	Efficient performance with reliable temperature stability	





## FS408BLBI7SSHV Specifications:

Overview		
Height of Cabinet	33.5" (85 cm)	
Height to Hinge Cap	34.0" (86 cm)	
Width	19.25" (49 cm)	
Depth	21.38" (54 cm)	
Depth with door at 90°	39.5" (100 cm)	
Capacity	2.8 cu.ft. (79 L)	
Defrost Type	Manual	
Door	Stainless Steel	
Cabinet	Black	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Amps	1.6	
Voltage/Frequency	115 V AC/60 Hz	
Weight	64.0 lbs. (29 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101036946	
Freezer		
Door Swing	RHD	
Reversible	Factory Reversible	
Height Adjustable	1	
Interior Height	26.38" (67 cm)	
Interior Width	14.0" (36 cm)	
Interior Depth	16.75" (43 cm)	
Thermostat Type	Dial	
Refrigerant Type	R134a	
Refrigerant Amount	3.0 oz.	
High Side PSI	210.0	
Low Side PSI	105.0	
Level Legs	2	
Interior Drawers	Yes	
Drawers Qty	4	



