

VT125



33.25" x 55.5" x 28.63" (H x W x D)

Laboratory chest freezer capable of -30° C(-22° F) operation

Highlights:

Commercially listed to NSF-7 standards and meets UL-471

Chest freezer with generous 14.1 cu.ft. storage capacity

Factory installed lock provides security you can count on

Product Features:

Commercially approved	UL-S listed to NSF-7 commercial standards and meets UL commercial standard 471
-30° (-22° F) capable	Low temperature operation ideal for vaccines, pharmaceuticals, and long-term preservation of frozen food
Large capacity	14.1 cu.ft. of storage space inside
Factory installed lock	Keep contents secure with a front lock on the door
Digital thermostat	Electronic controls for precise temperature management
Alarm with NIST calibrated temperature display	Audible alarm sounds to warn of temperature variations with a digital readout of the interior temperature
Manual defrost	Temperatures remain stable with an energy efficient manual defrost system
Corner protectors	Exterior protection important in high traffic settings
100% CFC free	Environmentally friendly design does not contain ozone-damaging chemicals

VT125 Specifications:

Overview	
Height of Cabinet	33.25" (84 cm)
Width	55.5" (141 cm)
Depth	28.63" (73 cm)
Capacity	14.1 cu.ft. (399 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	UL-S
Amps	1.49
Voltage/Frequency	115 V AC/60 Hz
Shipping Weight	250.0 lbs. (113 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101009247
Freezer	
Door Swing	Lift-Up
Interior Height	26.25" (67 cm)
Interior Width	48.0" (122 cm)
Interior Depth	21.5" (55 cm)
Thermostat Type	Digital
Refrigerant Type	R600a
Refrigerant Amount	3.53 oz.
High Side PSI	150.0
Low Side PSI	54.0
Compressor Step Height	9.25" (23 cm)
Compressor Step Width	9.38" (24 cm)
Compressor Step Depth	21.5" (55 cm)

