

VT65



33.5" x 23.63" x 23.5" (H x W x D)

Built-in undercounter laboratory freezer capable of -30° C (-22° F) operation

Highlights:

- Commercially listed to NSF-7 standards
- Precise temperature control with a digital thermostat
- Factory installed lock provides security you can count on

Product Features:

Built-in capable	Front-breathing system allows the unit to be used built-in
Commercially approved	Meets NSF-7 commercial standards
Slim counter height dimensions	24" footprint fits easily in space-challenged facilities
-30° C (-22° F) capable	Low temperature operation ideal for vaccines, pharmaceuticals, and long-term preservation of frozen food
Three slide-out drawers	Conveniently organize your items while keeping the temperature stable when the door is opened
Factory installed lock	Keyed lock offers convenient security
Digital thermostat	Electronic controls for precise temperature management
Alarm with temperature display	Provides external temperature readout and includes programmable alarm to warn of temperature variations
Manual defrost	No temperature fluctuations with an energy efficient manual defrost system

## VT65 Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Shipping Weight	118.0 lbs. (54 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101009223
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	2.76 oz.
Interior Drawers	Yes
Drawers Qty	3
Temperature Range	-20°C to -30°C

