

VT65ML7BI



33.5" x 23.63" x 23.5" (H x W x D)

Commercial built-in undercounter medical all-freezer capable of -25° C operation, with front-mounted lock

Highlights:

Factory-installed lock provides security you can count on

Flexible design allows built-in or freestanding use

-25° C operation for safe storage of temperature sensitive materials

Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinets
Fully finished white cabinet	Allows the unit to be used freestanding
Factory installed lock	Keep contents secure with a key lock on the door
Slim undercounter dimensions	Less than 24 inches wide to fit tight spaces
-25° C capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
Manual defrost	Static cooling system for improved temperature stability
Three removable storage baskets	Conveniently organize your items while keeping the temperature stable when the door is opened
Adjustable thermostat	Manage the interior temperature with ease and accuracy

VT65ML7BI Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	46.13" (117 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Weight	105.0 lbs. (48 kg)
Shipping Weight	118.0 lbs. (54 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101043159
Freezer	
Door Swing	RHD
Reversible	Yes
Height Adjustable	1
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Dial
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.0" (15 cm)
Compressor Step Width	17.75" (45 cm)
Compressor Step Depth	6.0" (15 cm)

Temperature Range	-12°C to -25°C
Sound Level	33 dB

