

VT65ML7CSS



33.25" x 23.75" x 23.5" (H x W x D)

Commercial built-in medical all-freezer capable of -25° C operation in complete stainless steel with front lock

Highlights:

- ETL-S listed to NSF-7 commercial standards
- 25° C operation for safe storage of temperature sensitive materials
- Factory-installed lock provides security you can count on

Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments
Slim undercounter dimensions	Less than 24 inches wide to fit tight spaces
Complete stainless steel exterior	Durable elegance that's easy to clean
Professional towel bar handle	A curved stainless steel handle provides generous room for a comfortable grip
Factory installed lock	Keyed lock for a secure interior
-25° C capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
Manual defrost	Static cooling system for improved temperature stability
Three removable storage baskets	Conveniently organize your items while keeping the temperature stable when the door is opened
Adjustable thermostat	Manage the interior temperature with ease and accuracy

VT65ML7CSS Specifications:

Overview	
Height of Cabinet	33.25" (84 cm)
Width	23.75" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.5" (65 cm)
Depth with door at 90°	45.25" (115 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Weight	105.0 lbs. (48 kg)
Shipping Weight	147.0 lbs. (67 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101043289
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Height Adjustable	1
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Dial
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.0" (15 cm)
Compressor Step Width	17.75" (45 cm)
Compressor Step Depth	6.0" (15 cm)

Temperature Range -12°C

