accucold

VT65MLBIPLUSADA

32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant 24" wide all-freezer for built-in use, manual defrost with a thermometer, lock, and -25ºC capability

Highlights:

32" height fits under lower ADA compliant counters

Flexible design allows built-in or freestanding use in 24 wide spaces

Factory installed lock provides security you can count on

Product Features:

ADA compliant	32" high to fit under lower ADA compliant counters
Built-in capable	Make the best use of space by installing your appliance under the counter
Factory installed lock	Keyed lock for secure interior
Thermometer	Thermometer provides external readout of current and high/low temperatures
Pull-out drawers	Clear baskets for convenient and separated storage
-25ºC capable	Low temperature capability ideal for certain sensitive items
Access port	Unit comes with a factory installed probe hole for users to connect their own monitoring equipment
Digital thermostat	Electronic controls located in the front kickplate for easy and intuitive temperature management
Matching refrigerator available	Pair with FF6LBIPLUSADA for a complete ADA compliant undercounter set

accucold

VT65MLBIPLUSADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	24.25" (62 cm)
Depth with door at 90°	45.13" (115 cm)
Capacity	3.2 cu.ft. (91 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101038599
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Shelf Type	Glass
Thermostat Type	Digital
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.5" (44 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	-12ºC to -25ºC