

FS30LVAC



24.63" x 18.5" x 17.75" (H x W x D)

Countertop vaccine storage all-freezer with digital thermostat, temperature alarm, hospital grade cord, self-closing door, and front lock

Highlights:

Medical grade design conforms with CDC guidelines for vaccine storage

Compact size is ideal for countertop use

Digital thermostat ensures more precision in temperature control

Product Features:

Compact dimensions	Sized for easy use on top of counters
Digital thermostat	Electronic controls ensure easy and intuitive temperature management, with a readout in Celsius or Fahrenheit
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
NIST calibrated temperature display	Alarm includes NIST calibrated display of the current interior and high/low temperature to the nearest tenth of a degree
Self-closing door	Door closes automatically when opened at angles less than 90°
3/8" access port	Unit comes with a factory installed probe hole for users to connect their own monitoring equipment
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Manual defrost	Static cooling system for improved temperature stability
Factory installed lock	Keyed lock for a secure interior

FS30LVAC Specifications:

Overview	
Height of Cabinet	26.25" (67 cm)
Height to Hinge Cap	24.63" (63 cm)
Width	18.5" (47 cm)
Depth	17.75" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.8 cu.ft. (51 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	50.0 lbs. (23 kg)
Shipping Weight	68.5 lbs. (31 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101032917
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	18.63" (47 cm)
Interior Width	13.38" (34 cm)
Interior Depth	13.0" (33 cm)
Shelf Type	Wire
Shelf Qty	2
Thermostat Type	Digital
Refrigerant Type	R600a
Refrigerant Amount	0.8 oz.
Level Legs	2
Compressor Step Height	8.0" (20 cm)
Compressor Step Width	13.38" (34 cm)
Compressor Step Depth	5.75" (15 cm)
Temperature Range	-20 to -15°C

