accucold

ARS6PV-AFZ5PVBIADASTACKLHD



Product Features:

Performance Series Refrigerator-Freezer Purpose-built all-refrigerator and all-freezer for vaccine storage in medical, pharmaceutical, Combination and life science applications Purpose-built design Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines +/-1°C Variation The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period Space-saving design Allows you to create a full refrigerator-freezer with independent controls in a slim-fitting footprint Easy assembly Unit ships in three boxes for customer to install the StackRack on the bottom refrigerator/freezer and place and secure the other unit on top Antimicrobial silver ion-coated handles Powder-coated handles with naturally occurring silver ions to help reduce the spread of germs Adjustable temperature Intuitive controls let you adjust the interior temperature between +2 to +8°C (refrigerator) and -30° to -10°C (freezer) Visual and audible alarms alert if the interior temperature rises or falls out of set range Temperature alarms

Semate Alarmanotaelevision, FELIX STORCH, Flectronic controller is equipped with a volt-free contact for alarm forwarding to an external 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893690016Faxsterna (contact locat contact locat with the contact for alarm forwarding to an external www.summitappliance.com

64" x 23.38" x 25" (H x W x D)

PHARMA-VAC Performance Series stacked combination of ARS6PV vaccine all-refrigerator and AFZ5PVBIADA manual defrost all-freezer

Highlights:

Purpose-built design to store medication, pharmaceuticals, and other sensitive materials

Independent refrigerator and freezer storage in one slimfitting footprint for space-challenged facilities

Intelligent microprocessor digital temperature controller for optimum temperature management

accuceld

ARS6PV-AFZ5PVBIADASTACKLHD Specifications:

| Overview | |
|---|--|
| Nominal Height | 64.0" (163 cm) |
| Height of Cabinet | 64.0" (163 cm) |
| Nominal Width | 24.0" (61 cm) |
| Width | 23.38" (59 cm) |
| Width with Door Open | 23.88" (61 cm) |
| Nominal Depth | 25.0" (64 cm) |
| Depth | 25.0" (64 cm) |
| Depth with Handle | 26.75" (68 cm) |
| Depth with door at 90° | 47.0" (119 cm) |
| Capacity | 9.88 cu.ft. (280 L |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Voltage/Frequency | 115 V AC/60 Hz |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| UPC | 761101104157 |
| Refrigerator-Freezer | |
| Door Swing | LHD |
| Reversible | No |
| Adjustable Shelves | Yes |
| Interior Light | Yes |
| Refrigerator - Interior Height | 24.5" (62 cm |
| Refrigerator - Interior Width | 20.0" (51 cm) |
| Refrigerator - Interior Depth | 17.0" (43 cm) |
| Refrigerator - Capacity | 6.0 cu.f |
| | |
| Refrigerator - Shelf Type | Wire |
| Refrigerator - Shelf Type Refrigerator - Shelf Qty | |
| 0 71 | 2 |
| Refrigerator - Shelf Qty Refrigerator - Temperature | 2 to 8°C |
| Refrigerator - Shelf Qty Refrigerator - Temperature Range Refrigerator - Refrigerant | 2 to 8°C R600a |
| Refrigerator - Shelf Qty Refrigerator - Temperature Range Refrigerator - Refrigerant Type Refrigerator - Refrigerant | 2 to 8°C R600a 1.66 oz |
| Refrigerator - Shelf Qty Refrigerator - Temperature Range Refrigerator - Refrigerant Type Refrigerator - Refrigerant Amount | Wire 2 to 8°C R600a 1.66 oz 22.5" (57 cm 18.0" (46 cm |

| Freezer - Capacity | 3.88 cu.ft |
|---------------------------------|--------------|
| Freezer - Shelf Type | Wire |
| Freezer - Shelf Qty | 4 |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Freezer - Temperature Range | -30 to -10⁰C |
| Freezer - Refrigerant Type | R290a |
| Freezer - Refrigerant Amount | 1.73 oz. |
| | |



