



SBC58BLIFFLTWCFADALHD



32" x 23.63" x 22.38" (H x W x D)

Built-in 24" wide ADA-compliant dual tap coffee dispenser with panel-ready door and removable tap system for non-permanent installation

Highlights:

Innovative Floating Tap lets you create a complete undercounter kegerator without modifying your countertop

Easy-to-install + removable tap system allows you to change your space as needed

Just 32" high for an easy fit under lower ADA compliant counters

Product Features:

| | |
|---|---|
| 24" Wide Built-In Floating Tap Beer Dispenser | Dual tap kegerator with a remote tapping system that includes everything you need to pour draft beer without modifying your countertop |
| Commitment-free design | Non-permanent draft tower is separated from the actual kegerator and designed for temporary installation on counter surfaces, allowing you to remove as needed |
| ADA compliant design | 32" height allows easy installation under lower ADA compliant counters |
| Built-in capable | Designed for installation under the counter |
| No drilling needed | Tower is connected to the removable tap kit that does not need to be permanently attached to your countertop |
| Panel-ready door | Integrated stainless steel door frame allows you to mount full overlay panels over the door to create a custom look that can blend into cabinetry with no exposed frame (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.) |
| Dual tap system | Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs |
| Easy installation | No tools or equipment needed for fast setup and easy removal |
| Convertible to a refrigerator | Includes a tap hole cover, glass shelves, and a scalloped steel bottle rack to all you to convert the kegerator into a traditional all-refrigerator |



SBC58BLIFLTCFADALHD Specifications:

| Overview | |
|----------------------------|---------------------|
| Height of Cabinet | 31.88" (81 cm) |
| Height to Hinge Cap | 32.0" (81 cm) |
| Width | 23.63" (60 cm) |
| Depth | 22.38" (57 cm) |
| Depth with Handle | 24.3" (62 cm) |
| Depth with door at 90° | 44.5" (113 cm) |
| Capacity | 5.8 cu.ft. (164 L) |
| Defrost Type | Automatic |
| Door | Panel-Ready |
| Cabinet | Black |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Energy Usage/Year | 239.0kWh/year |
| Amps | 0.8 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 180.0 lbs. (82 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101146027 |
| Kegeerator | |
| Door Swing | LHD |
| Height Adjustable | No |
| Tap Kit | Yes |
| Number of Taps | 2 |
| Adjustable Shelves | Yes |
| Shelf Type | Glass and Scalloped |
| Shelf Qty | 4 |
| Thermostat Type | Dial |
| Interior Light | Yes |
| Refrigerant | R600a |
| Refrigerant Amount | 0.64 oz. |
| Inter Height | 27.0" (69 cm) |
| Interior Width | 21.0" (53 cm) |
| Interior Depth | 17.75" (45 cm) |
| Compressor Step Height | 6.5" (17 cm) |

| | |
|-----------------------|---------------|
| Compressor Step Width | 21.0" (53 cm) |
| Compressor Step Depth | 5.5" (14 cm) |
| Level Legs Qty | 4 |
| Temperature Range | 36 to 46°F |

