# 

## **BIM44GIFADARHD**



#### 32.38" x 14.5" x 23.5" (H x W x D)

ADA compliant built-in undercounter NSF-listed automatic defrost clear icemaker with integrated door frame to accept full overlay panels and an internal pump

#### **Highlights:**

Commercial ENERGY STAR certification

32 3/8" height for use in ADA compliant settings

Flexible design allows built-in or freestanding use in 15" wide spaces

#### **Product Features:**

ENERGY STAR certified commercial performance	Efficient performance for commercial use
ADA compliant	32 3/8" height fits under lower ADA compliant counters
Commercially approved	NSF listed for use in commercial establishments
Built-in pump	Internal pump allows more flexibility in placing the unit
Built-in capable	Make the best use of space by installing your appliance under the counter
Panel-ready door	Stainless steel door frame accepts full overlay panels to match adjacent cabinetry (panel size: 27 7/8" H x14 5/8" W and at least $3/4$ " thick; maximum weight: 10 lbs.)
Clear ice cube production	Clear cubes offer the perfect cooling of your beverages; NOTE: ice is produced in sheets and can easily be broken into cubes using the provided scoop
Automatic defrost	Reduced maintenance with auto defrost system
Insulated storage bin	Ice stays frozen longer inside this cold-protected bin

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com

 $\checkmark$ 





### BIM44GIFADARHD Specifications:

Overview	
Nominal Height	32.0" (81 cm)
Height of Cabinet	32.38" (82 cm)
Nominal Width	15.0" (38 cm)
Width	14.5" (37 cm)
Nominal Depth	24.0" (61 cm)
Depth	23.5" (60 cm)
Defrost Type	Automatic
Door	Panel-Ready
Cabinet	Black
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	NSF
Amps	4.8
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101093192
le emelsen	
Icemaker	
Door Swing	RHD
	RHD Yes
Door Swing	
Door Swing Drain Required	Yes
Door Swing Drain Required Daily Ice Production	Yes 50.0 lbs. (23 kg)
Door Swing Drain Required Daily Ice Production Ice Storage Capacity	Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg)
Door Swing Drain Required Daily Ice Production Ice Storage Capacity Ice Shape	Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube
Door Swing Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube	Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 7/8" x 7/8" x 7/8"
Door Swing Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Number of Ice Cube Sizes	Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 7/8" x 7/8" x 7/8" 1
Door Swing Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Number of Ice Cube Sizes Fan Type	Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 7/8" x 7/8" x 7/8" 1 Exterior
Door Swing Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Number of Ice Cube Sizes Fan Type Refrigerant Type	Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 7/8" x 7/8" x 7/8" 1 Exterior R134a
Door Swing Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Number of Ice Cube Sizes Fan Type Refrigerant Type Refrigerant Amount	Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 7/8" x 7/8" x 7/8" 1 Exterior R134a 3.88 oz.
Door Swing Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Number of Ice Cube Sizes Fan Type Refrigerant Type Refrigerant Amount High Side PSI	Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 7/8" x 7/8" x 7/8" 1 Exterior R134a 3.88 oz. 350.0
Door Swing Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Size of Cube Number of Ice Cube Sizes Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 7/8" x 7/8" x 7/8" 1 Exterior R134a 3.88 oz. 350.0 130.0
Door Swing Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Number of Ice Cube Sizes Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Interior Height	Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 7/8" x 7/8" x 7/8" 1 Exterior R134a 3.88 oz. 350.0 130.0 18.5" (47 cm)
Door Swing Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Size of Cube Number of Ice Cube Sizes Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Interior Height Interior Width	Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 7/8" x 7/8" x 7/8" 1 Exterior R134a 3.88 oz. 350.0 130.0 18.5" (47 cm) 12.0" (30 cm)



