SUMMIT

ASDS2413IFLHD



32" x 23.38" x 17.75" (H x W x D)

Shallow depth built-in undercounter ADA compliant allrefrigerator with panel-ready door, stainless steel interior, black cabinet, lock, and digital controls

Highlights:

Panel-ready door lets you customize the unit for a seamless look that integrates into your kitchen

Uniquely shallow depth under 18" for an easy fit in kitchen islands

32" height fits under lower ADA compliant counters

Product Features:

24" wide all-refrigerator	3.1 cu.ft. interior for residential or commercial cold storage	
Less than 18" deep	Unique 17.75" shallow depth is ideal for wet bars, island kitchens, and other undercounter areas with limited footprint space	
ADA compliant design	32" height allows easy installation under lower ADA compliant counters	
Adjustable height	Leveling legs can be extended up to 2", with a slide-out kickplate that allows you to raise the overall height from 32" up to 34" if used under more standard sized cabinets	
Built-in capable	Front-breathing design lets you make the best use of space by installing your appliance under the counter	
Stainless steel interior	Walls and floor are constructed from stainless steel for added strength and easy cleanup	
Panel-ready door	European style articulating door hinge allows the installation of overlay panels, allowing you to customize the refrigerator door or blend it into your cabinetry design; panel size: 23.4" W x 28.38" H and at least 3/4" thick; 10 lbs. maximum; customers provide their own handles	
Factory installed lock	Keyed lock for a secure interior (2 keys included)	
Frost-free operation	No-frost operation for minimum user maintenance	



ASDS2413IFLHD Specifications:

Overview			
Nominal Height	32.0" (81 cm)		
Height of Cabinet	32.0" (81 cm)		
Nominal Width	24.0" (61 cm)		
Width	23.38" (59 cm)		
Nominal Depth	18.0" (46 cm)		
Depth	17.75" (45 cm)		
Depth with door at 90°	40.0" (102 cm)		
Capacity	3.1 cu.ft. (88 L)		
Defrost Type	Frost-Free		
Door	Panel-Ready		
Cabinet	Black		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Sanitation	ETL-S		
Energy Usage/Year	215.0kWh/year		
Amps	1.0		
Voltage/Frequency	115 V AC/60 Hz		
Weight	89.0 lbs. (40 kg)		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
UPC	761101092782		
Refrigerator Features			
Sabbath Mode	Yes		
Door Swing	LHD		
Reversible	No		
Height Adjustable	Yes		
Shelf Type	Chrome		
Shelf Qty	3		
Adjustable Shelves	Yes		
Thermostat Type	Digital		
Fan Type	Interior and Exterior		
Refrigerant Type	R600a		
Refrigerant Amount	1.38oz.		
High Side PSI	270.0		
Low Side PSI	105.0		
Level Legs Qty	4		
Interior Light	Yes		

Temperature Range	36 to 43°F
Sound Level	32.9 dB
Dimensions	
Interior Height	24.25" (62 cm)
Interior Width	19.5" (50 cm)
Interior Depth	12.25" (31 cm)
Compressor Step Height	3.75" (10 cm)
Compressor Step Width	19.5" (50 cm)
Compressor Step Depth	4.25" (11 cm)



